

# Heat Treated Wireline Drill Rods



— Wireline  
drill rod

Description	Length	Part No.	Weight	
			lb	kg
A W/L	2'	30-31-202	6.00	2.7
A W/L	5'	30-31-205	15.50	20.7
A W/L	10'	30-31-210	31.30	14.2
B W/L	2'	30-31-302	8.00	3.6
B W/L	5'	30-31-305	20.00	9.1
B W/L	10'	30-31-310	40.00	18.2
N W/L	2'	30-31-402	10.50	4.8
N W/L	5'	30-31-405	25.00	11.4
N W/L	10'	30-31-410	51.00	23.2
NC W/L*	10'	30-32-410	45.00	20.4
NM W/L (i.d. groove)	2'	30-33-402	10.50	4.8
NM W/L (i.d. groove)	5'	30-33-405	25.00	11.4
NM W/L (i.d. groove)	10'	30-33-410	57.00	23.2
H W/L	2'	30-31-502	15.50	7.0
H W/L	5'	30-31-505	38.50	17.5
H W/L	10'	30-31-510	77.00	35.0
HC W/L*	10'	30-32-510	59.50	27.0
HM W/L (i.d. groove)	2'	30-33-502	15.50	7.0
HM W/L (i.d. groove)	5'	30-33-505	38.50	17.5
HM W/L (i.d. groove)	10'	30-33-510	77.00	35.0
HWL	2'	30-51-502	15.00	6.8
HWL	5'	30-51-505	38.00	17.3
HWL	10'	30-51-510	76.50	34.8
HMC W/L*	10'	30-52-510	63.16	28.7
P W/L	2'	30-31-602	21.10	9.6
P W/L	5'	30-31-605	54.10	24.6
P W/L	10'	30-31-610	104.60	48.0
HW W/L	2'	30-34-602	23.12	10.5
HW W/L	5'	30-34-605	57.80	26.3
HW W/L	10'	30-34-610	115.60	52.5

\*W/L "C" series = upset ends.

Metric				
A W/L	0.75 m	30-36-202	6.00	2.7
A W/L	1.50 m	30-36-205	15.00	6.8
A W/L	3.00 m	30-36-210	30.00	13.6
B W/L	0.75 m	30-36-302	7.80	3.6
B W/L	1.50 m	30-36-305	19.10	8.7
B W/L	3.00 m	30-36-310	39.00	17.7
N W/L	0.75 m	30-36-402	10.20	4.6
N W/L	1.50 m	30-36-405	24.00	10.9
N W/L	3.00 m	30-36-410	51.00	23.2
NM W/L (i.d. groove)	0.75 m	30-38-402	10.20	4.6
NM W/L (i.d. groove)	1.50 m	30-38-405	24.00	10.9
NM W/L (i.d. groove)	3.00 m	30-38-410	51.00	23.2
H W/L	0.75 m	30-36-502	15.20	6.9
H W/L	1.50 m	30-36-505	37.80	17.2
H W/L	3.00 m	30-36-510	76.00	34.5
HM W/L (i.d. groove)	0.75 m	30-38-502	15.20	6.9
HM W/L (i.d. groove)	1.50 m	30-38-505	37.80	17.2
HM W/L (i.d. groove)	3.00 m	30-38-510	76.00	34.5
HW W/L	0.75 m	30-39-602	22.80	10.4
HW W/L	1.50 m	30-39-605	57.00	25.9
HW W/L	3.00 m	30-39-610	114.00	51.8